

ALFA TP-80H (AL102016)

ΘΕΡΜΙΚΟΣ ΕΚΤΥΠΩΤΗΣ



ELZAB¹⁹⁶⁹
HELLAS

Γενικά χαρακτηριστικά

- ✓ Πολύ γρήγορη εκτύπωση έως 300 mm/s
- ✓ 2 διεπαφές σύνδεσης (USB / LAN)
- ✓ Αυτόματος κόφτης χαρτιού
- ✓ Θερμικό χαρτί 80 mm
- ✓ Ενσωματωμένο μεγάφωνο για σηματοδότηση της εκτύπωσης



**MULTI
INTERFACE**



**300mm/s
SPEED**



**80mm
THERMAL
PAPER**



**THERMAL
PAPER**



Τύπος	Θερμικός εκτυπωτής
Τρόπος Λειτουργίας	Εκτύπωση επιβεβαιώσεων και πληροφοριών με την δυνατότητα κοψίματος του χαρτιού
Διαπαφές	USB / ETHERNET / WIFI RJ τύπος σύνδεσης συρταριού
Μηχανισμός εκτύπωσης	Θερμικός, μέγιστη ταχύτητα εκτύπωσης έως 300 mm/s
Αυτόματος κόπτης	Ναι
Πλάτος εκτύπωσης	72 mm
Ανάλυση	576 Dots/Line or 512 Dots/Line (203 dpi, 8dots/mm)
Barcodes	1D bar code: UPC-A/UPCE/ JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128 2D barcode: Δεν υποστηρίζεται
Κωδικοσελίδα	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/ Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/ (PC864)/(Vietnam)/(Thai)
Τροφοδοσία	Power Adaptor: Input: AC 100V-240V,50-60Hz / Output: DC 24V/2.5A Cash Drawer output: DC 24V/1A
Διάρκεια κεφαλής εκτύπωσης	100 KM
Διάρκεια κόφτη	1.000.000 φορές
Βάρος	1.05 kg
Εγγύηση	24 μήνες

Printer Parameters:

Item		Parameters
Print parameters	Printing Method	Thermal Line
	Printing width	72mm
	Resolution	576 Dots/Line or 512 Dots/Line (8dots/mm,203dpi)
	Print speed	300mm/Second
	Interface	Internet (100M)+USB+COM;Internet (100M) +USB+WIFI;USB+GPRS;USB+COM;USB+ Bluetooth
	Line Spacing	3.75mm (Can adjust line spacing by command)

	Line No.	FontA-48Lines/FontB-64Lines/Simple, traditional Chinese-24 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANK character,Font A:1.5×3.0mm (12×24 dots) ;Font B:1.1×2.1mm (9×17 dots) Simplified/Traditional Chinese3.0×3.0mm(24×24 dots)
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/ PC865/WestEurope/Greek/Hebrew/ EastEurope/Iran/WPC1252/PC866/PC852/ PC858/IranII/Latvian/Arabic/PT151,1251/ PC737/WPC/1257/ThaiVietnam/PC864/ PC1001/(Latvian)/(PC1001)/(PT151,1251)/ (WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D bar code: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/ CODE39/ITF/CODABAR/CODE93/CODE128 2D barcode: QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print
Cutter	Cutter Function	Full cut/Half cut
Paper	Type	Thermal
	Width	79.5±0.5mm
	Diameter	≤80mm

Print commands	Commands	ESC/POS
Power	Power Adaptor	Input: AC 100V-240V,50 ~ 60Hz Output: DC 24V/2.5A
	Cash Drawer output	DC 24V/1A
Buffer	Input Buffer	2048K bytes
	NV Flash	256K bytes
physical characteristics	Weight	1.2KG
	Dimension	186*145*133(MM)
Environment	Working	Temp: 5 ~ 45 ℃ Humidity: 10 ~ 80%
	Storage	Temp: -10 ~ 50 ℃ Humidity: 10 ~ 90% (No dew)
Reliability parameter	Print Head Life	100KM (print density≤12.5)
	Cutter Life	1000,000times
Software	Driver	Android,IOS,Linux,Win2000,Win2003,WinXP, Win7,Win8,Win8.1