

TECHNICAL SPECIFICATIONS

PIXMA G5040

GENERAL SPECIFICATIONS

Functions

Wi-Fi, Ethernet, Print

PRINTER SPECIFICATIONS

Print Resolution

Up to 4800^[1] x 1200 dpi

Print Technology

2 FINE Cartridges (Black and Colour)
Refillable ink tank printer

Mono Print Speed

Approx. 13.0 ipm^[2]

Colour Print Speed

Approx. 6.8 ipm^[2]

Photo Print Speed

Borderless 10x15cm : Approx. 45 seconds^[3]

Borderless Printing

Yes A4, LTR, 4"x6", 5"x7", 7"x10", 8"x10",
Square (5"x5", 4"x4", 89x89mm)

Two Sided Printing

Auto Duplex Print (A4, A5, B5, Letter - Plain Paper)

CARTRIDGES AND YIELDS

Standard Ink Cartridges

GI-40 <PGBK>
GI-40 <C>
GI-40 <M>
GI-40 <Y>

Cartridge Yield (Plain paper)

A4 colour documents printing^[4]

Black: 6,000 pages

Colour: 7,700 pages

* Estimated supplemental yield

Cartridge Yield (Photo print)

10x15cm colour photo printing^[5]

Colour: 2,200 photos

* Estimated supplemental yield

PAPER SUPPORT

Paper Types

Plain Paper
High Resolution Paper (HR-101N)
Photo Paper Plus Glossy II (PP-201)
Photo Paper Pro Platinum (PT-101)
Photo Paper Pro Luster (LU-101)
Photo Paper Plus Semi-gloss (SG-201)
Glossy Photo Paper "Everyday Use" (GP-501)
Matte Photo Paper (MP-101)
Envelope

Maximum Paper Input

Rear Tray: Max. 20 sheets (photo paper) or Max.
100 sheets (plain paper)
Cassette: Max. 250 sheets (plain paper)

Paper Sizes

Rear Tray: A4, A5, B5, LTR, LGL, 4"x6", 5"x7", 7"x10",
8"x10",
Envelopes (DL, COM10), Square (5" x 5",
4"x4", 89x89mm), Card Size (91 x 55mm)
[Custom size] width 55mm - 215.9 mm, length
89mm - 67.6mm

Cassette: A4, A5, B5, LTR
[Custom size] width 148.0 mm - 215.9 mm, length
210mm - 297mm

Paper Weight

Rear Tray: Plain paper: 64 - 105 g/m²
Canon photo paper: up to 300 g/m² (Photo Paper
Pro Platinum PT-101)

Cassette: Plain paper: 64 - 105 g/m²

INTERFACE

Display Type & Size

Full Dot LCD

Display Languages

32 Languages Selectable: Japanese/English
(mm & inch)/German/French/Italian/Spanish/Dutch/
Portuguese/Norwegian/Swedish/Danish/Finnish/
Russian/Czech/Hungarian/Polish/Slovene/Turkish/
Greek/Simplified Chinese/Traditional
Chinese/Korean/Indonesian/Slovakian/Estonian/
Latvian/
Lithuanian/Ukrainian/Romanian/
Bulgarian/Croatian/Vietnamese

Interface Type - PC / Mac

Hi-Speed USB (B Port)
Ethernet: 10/100Mbps (auto switchable)
Wi-Fi: IEEE802.11 b/g/n
Wi-Fi Security: WPA-PSK, WPA2-PSK, WEP,
Administration password
Wireless LAN Frequency Band: 2.4GHz

Interface Type - Other

Canon PRINT Inkjet/SELPHY app
Easy-PhotoPrint Editor
Message In Print app
PIXMA Cloud Link
Canon Print Service Plugin (Android)
Google Cloud Print
Apple AirPrint
Wireless Direct
Access Point Mode
LAN/WLAN PictBridge
Mopria (Android)

SOFTWARE

Supported Operating Systems

Windows 10, Windows 8.1, Windows 7 SP1

Operation can only be guaranteed on a PC with
pre-installed Windows 7 or later.

Printer driver and IJ Network Device Setup Utility are
available with following OS.
Windows Server 2008 R2 SP1 - Windows Server 2012
R2 - Windows Server 2016

OS X 10.10.5~OS X 10.11 - macOS 10.12~macOS
10.14

iOS, Android, Windows 10 Mobile

Supported Mobile Systems

Minimum System Requirements

Windows: 2.0GB or more

Mac: 1.0GB or more

Note: for bundled software installation. The
necessary amount of hard disk space required.
Display: 1024 x 768 XGA

Software Included

Printer Driver
IJ Printer Assistant Tool
Easy-PhotoPrint Editor (download)

PHYSICAL FEATURES

Weight

approx. 6.5 kg

Dimensions (W x D x H)

approx. 403 x 369 x 166 mm

Acoustic Noise Levels

approx. 50.5dB(A)^[6]

Operating Temperature

5-35°C

Operating Humidity

10-90%RH (no dew condensation)

Power Source

AC 100-240V, 50/60Hz

Power Consumption

Off: Approx. 0.3W

Standby (connected to PC via USB): Approx. 0.8W

Standby (all parts connected): Approx. 1.6W

Time to enter Standby mode: 11 min 10sec

Printing (USB connection to PC): Approx. 21W^[7]

0.2kWh^[8]

Typical Electricity Consumption (TEC)

Footnotes

^[1] Ink droplets can be placed with a minimum pitch of 1/4800 inch

^[2] A4 document print speed on plain paper is measured based on average of ESAT in
Office Category Test of ISO/IEC 24734 standard.

^[3] Photo print speed is based on default driver setting using ISO/JIS-SCID N2 standard
on Canon Photo Paper Plus Glossy II and does not take into account data
processing time on host computer.

^[4] Page Yield is the estimated value based on Canon individual test method using
the ISO/IEC 24712 chart and continuous printing simulation with the replacement
ink bottles after initial setup.

^[5] Page Yield is the estimated value based on Canon individual test method using
the ISO/IEC 29103 chart and continuous printing simulation with the replacement
ink bottles after initial setup.

^[6] Plain Paper(A4, B/W). Acoustic Noise is measured based on ISO7779 standard.

^[7] Print: When printing ISO/JIS-SCID N2 on A4 size plain paper using default settings.

^[8] Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit
will be constantly switched among operational mode, sleep mode, and power-off mode
for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days
within the same week. The TEC value of this product is calculated by Canon on their own
accord using TEC measurement procedure regulated in International ENERGY STAR
Program.

Standard disclaimers

All specifications subject to change without notice.

Print speed may vary depending on system configuration, interface, software,
document complexity, print mode, page coverage, type of paper used etc.

Ink yield may vary depending on texts/photos printed, applications software used,
print mode and type of paper used. For yield information see
www.canon-europe.com/ink/yield

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered

trademarks of Microsoft Corporation in the United States and/or other countries.

Live for the story_

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2019