

Simply Smart.

P2500 Series
Monochrome Laser Printer

Print high quality documents on-the-go with the compact printer that is easy to use and easy to carry. Enjoy connectivity, space saving and budget friendly features from the mini printer that SMB, home users and office professionals rely on.



Business READY economical printer series

•1600 pages starter cartridge •Silvery-grey sleek exterior



Pantum Infinite Series

One step driver installation and direct printing



Compact and **Sleek Design**



Wi-Fi Connectivity and Mobile Printing



Office document direct print from mobile devices



Fast Print Speed











Model	P2509		P2509W
-------	-------	--	--------

Гесhnology	Electrophotographic monochrome laser	
Print speed	22 ppm (A4) / 23 ppm (Letter)	
First print out time	Less than 7.8s	
Maximum monthly volume	15,000 pages	
Recommended monthly volume	700 pages	
Resolution(dpi)	Max.1,200×1,200	
Printer language	GDI	
Duplex Mode	Manual	
er handling		
Paper input	150 pages	
Paper output Paper output	100 pages	
Paper output	Plain, Thick, Transparency, Cardstock, Label, Envelope, Thin	
Media size	A4, A5, A6, JIS B5, ISO B5, B6, Letter, Legal, Executive, Statement, Monarch envelope, DL envelope, C5 envelope, C6 envelope, NO.10 envelope, Japanese postcard, Folio, Oficio, Big 16k, 32k, 16k, Big 32k, ZL, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2	
Media weight	60~163g/m²	
eral		
Dimensions (W×D×H)	337 x 220 x 178 mm (13.27" x 8.66" x 7.01")	
Weight (with cartridge)	4.75kg (10.47lbs)	
Recommended environment	Temperature range: 10-32°C (50°F-90°F) Humidity range: 20% - 80%	
necommended environment		
Power		
	Humidity range: 20% - 80% 110V Model: AC100~127V (±10%); 50Hz/60Hz; 6A	
Power	Humidity range: 20% - 80% 110V Model: AC100~127V (±10%); 50Hz/60Hz; 6A 220V Model: AC220~240V (-15%,+10%), 50Hz/60Hz; 3A Printing: 52 dB	
Power	Humidity range: 20% - 80% 110V Model: AC100~127V (±10%); 50Hz/60Hz; 6A 220V Model: AC220~240V (-15%,+10%), 50Hz/60Hz; 3A Printing: 52 dB Standby: 30 dB Printing: Average 370W Ready: 38W	
Power Noise Power consumption	Humidity range: 20% - 80% 110V Model: AC100~127V (±10%); 50Hz/60Hz; 6A 220V Model: AC220~240V (-15%,+10%), 50Hz/60Hz; 3A Printing: 52 dB Standby: 30 dB Printing: Average 370W Ready: 38W Sleep Mode: Less than 2W Windows Server2003 / 2008 / 2012 / XP / Vista / Win 7 / Win 8 / Wins.1 / Win10 (32/64 Bit); Mac OS 10.7~10.13;	
Power Noise Power consumption Operating system compatibility Mobile Operating system compatibility	Humidity range: 20% - 80% 110V Model: AC100~127V (±10%); 50Hz/60Hz; 6A 220V Model: AC220~240V (-15%,+10%), 50Hz/60Hz; 3A Printing: 52 dB Standby: 30 dB Printing: Average 370W Ready: 38W Sleep Mode: Less than 2W Windows Server2003 / 2008 / 2012 / XP / Vista / Win 7 / Win 8 / Win8.1 / Win10 (32/64 Bit); Mac OS 10.7~10.13; Linux: Ubuntu12.04/14.04 (32/64 Bit)	
Power Noise Power consumption Operating system compatibility Mobile Operating system compatibility Connectivity	Humidity range: 20% - 80% 110V Model: AC100~127V (±10%); 50Hz/60Hz; 6A 220V Model: AC220~240V (-15%,+10%), 50Hz/60Hz; 3A Printing: 52 dB Standby: 30 dB Printing: Average 370W Ready: 38W Sleep Mode: Less than 2W Windows Server2003 / 2008 / 2012 / XP / Vista / Win 7 / Win 8 / Win8.1 / Win10 (32/64 Bit); Mac OS 10.7~10.13; Linux: Ubuntu12.04/14.04 (32/64 Bit)	
Power Noise Power consumption Operating system compatibility Mobile Operating system	Humidity range: 20% - 80% 110V Model: AC100~127V (±10%); 50Hz/60Hz; 6A 220V Model: AC220~240V (-15%,+10%), 50Hz/60Hz; 3A Printing: 52 dB Standby: 30 dB Printing: Average 370W Ready: 38W Sleep Mode: Less than 2W Windows Server2003 / 2008 / 2012 / XP / Vista / Win 7 / Win 8 / Win8.1 / Win10 (32/64 Bit); Mac OS 10.7~10.13; Linux: Ubuntu12.04/14.04 (32/64 Bit) iOS 7.0 and above; Android 4.4 and above Hi-Speed USB 2.0; WiFi: IEEE 802.11b/g/n	

Toner cartridge (1) PD-219 (Standard capacity toner: 1,600 pages)

What's in the box

Printer x 1/1600 pages starter cartridge x 1 / USB interface cable x 1 / Power cord x 1 / CD-ROM x 1 / Quick setup guide x 1

(1) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)

Copyright © 2019 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.

*Printer data based on Pantum internal testing.