

ZYWELL ZM-01

ΦΟΡΗΤΟΣ ΘΕΡΜΙΚΟΣ ΕΚΤΥΠΩΤΗΣ



- **Μοντέλο:** ZM-01
- **Ανάλυση:** 203 dpi (8 dots/mm)
- **Πλάτος χαρτιού:** 48mm/52mm/56mm/64mm/68mm/76mm/80mm
- **Διαστάσεις:** 115(D)x110(W)x50(H)mm
- **Barcode:**
 - 1D:** UPC-A, UPC-E, EAN-8, EAN-13, CODE 39, ITF, CODE 128, CODE 93
 - 2D:** QR code, PDF417
- **Μπαταρία:** Επαναφορτιζόμενη 7.4V
- **Εισαγωγή χαρτιού:** Easy paper loading
- **Ταχύτητα εκτύπωσης:** 80mm/s
- **OS:** Windows, Android, IOS



Σας παρουσιάζουμε το νέο μοντέλο φορητού εκτυπωτή τιμολογίων & αποδείξεων **ZYWELL ZM-01**.

Τα τεχνικά του χαρακτηριστικά συνδυάζουν υψηλή απόδοση και πρακτικότητα. Οι επιλογές συνδεσιμότητας (Bluetooth + USB) καθώς και η μεγάλη αυτονομία μπαταρίας εξασφαλίζουν αδιάλειπτη λειτουργία.





Paper roll capacity up to 45mm OD (Outside Diameter)



Support 80mm paper



ZM01
Mobile Thermal Printer

Press **Function** enter into menu as below

1. Print Test
2. Print Mode
3. GAP Calibrate
4. Density Set
5. Sleep Time
6. Off Time
7. Print Speed
8. System Info



POWER

FUNCTION

FEED

LED Screen



SPECIFICATIONS

Printing Method	Direct thermal
Print Speed	80mm/sec
Resolution	203 dpi (8 dots/mm)
Printing Width	72mm
Paper Width	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Barcode	1D & 2D
Interface	SERIAL+USB+WIFI or SERIAL+USB+BT
Input Buffer	256k bytes
NV Flash	2M bytes
Power Supply	AC 100V-240V 50/60HZ
Sensor	Paper out detectof, cover open detector, black mark detector,gap detector
Power	AC 100V-240V 50/60HZ, DC 24V/2.5A
Storage Temperature	From -10c To 60c
Operation Temperature	From 0c To 45c
Dimension	11 cm(W) x 5 cm(H) x 12 cm(D)
Weight	0.36 KG

Printing

Print Method	Direct Thermal
Print Speed	80mm/s
Resolution	203 dpi (8 dots/mm)
Printing Width	72mm
Paper separator(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Interface	SERIAL+USB+WIFI or SERIAL+USB+BT

Memory

Input buffer	256kbytes
NV Flash	2M

Fonts

Alphanumeric; Simplified Chinese, Traditional Chinese; 35 International Character Sets

Barcode

1D	UPC-A, UPC-E, EAN-8, EAN-13, CODE 39, ITF, CODE 128 , CODE 93
2D	QR code , PDF417

Detection

Sensors	Paper out detector, cover open detector, black mark detector,gap detector
---------	---

Power Supply

Input	AC 100V-240V 50/60HZ
Output	DC 5V, 1A

Battery

Paper

Paper Type	Thermal receipt paper
Paper Width	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper Thickness	0.053 ~ 0.15mm
Roll Dia	Max. Φ 50 mm (O.D)
Paper Load	Easy paper loading
Paper Cut	Manual tear

Physical Characteristics

Working Condition	-2°C ~ 52°C, 10% ~ 85% R.H, no-condensing
Storage Condition	-20 ~ 60°C, 5 ~ 90% R.H, no-condensing
Dimensions	115(L)×110(W)×50(H) mm

Net weight	0.36KG	Gross weight	0.5KG
Reliability			
Printing head	50KM		
Cutter	---		
Accessories			
	data cable,power adaptor,power code,paper roller,CD,manual,paper separator		
Packing			
Individual box	Dimension 23X15X6.5cm(LXWXH)	1unit/carton	
Master carton	Dimension 48X32X34cm(LXWXH)	20units/carton	
OS			
Emulation	ESC/POS		
Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/ OPOS/JPOS		
SDK	Android, IOS		